

## What is SR BLACK

- Main ingredient: Carbon black, Water.
- Carbon black, which is the raw material of sumi ink, absorbs light and convert it to heat to melt snow and ice faster.
- Experimental results shows no harmful impact on plants\* and glass.
- \* Bent grass and KOMATSUNA sprout



Application amount: 250ml/m (1 in 200 dilution)

No environmental impact on soil, metal, concrete and similar materials. Carbon black, which is the raw material of sumi ink, absorbs light and convert it to heat.

(Note: Snow melting water may turn black, depending on the spraying concentration.)



Application amount: Small dose

Application amount: Recommended dose

Area which calcium carbonate sprayed

SR BLACK save your time and money!

No driver and tractor required!

**SR Black has nearly** as effective as

Easytospray with drone or sprayer

It saves you time 1/2 up to
1/3 conparing to spraying with tractor

## How to use

- Water down "SR BLACK", mix it well and spray to snow surface.
- Recommended conc.
  - •1/200-1/600 dilution for sprayer.
  - •undiluted or 1/3 dilution for drone.
  - \*Effective conc is determined by amount of snowfall and weather.

## CAUTION

- •With high concentration, snow melts faster but black color may remain on snow.
- Amount of snow and weather may affect the result.
- •If on skin, wash with water.
- •If in eyes, rinse cautiously with water and get medical advice/attention.
- •Seal up and store in a cool, dry place away from direct sunlight.
- It may be frozen under -5℃ temperature.
- •Keep away from children.
- Both undiluted and diluted solution will not come off once it is on bulding or clothes.
- Do not drink.

Product number	Product name	Size	Product identifier (JAN)	Unit
CA11-903	SR BLACK	3L	4901427332704	1
CA11-980	SR BLACK	18L	4901427010558	1

- ♦The colors and textures represented within this catalogue are as close as the photographic and printing processes will allow.
- Colors and line widths are affected by the material to which they are applied. Always test first on a sample piece of material if precise color-matching is important.
- Kuretake reserves the right to alter specifications and make improvements to products without notice.

## **Kuretake** Est.1902

Kuretake Co.,Ltd. 576 Minamikyobate-cho, 7-chome, Nara-shi, 630-8670, Japan

Nara-shi, 630-8670, Japan TEL: +81.742.50.2055 FAX: +81.742.50.2077

URL: www.kuretake.co.jp

Kuretake ZIG Corporation

URL:www.kuretakezig.com